

AL34 EKOFLEKS - Facade acrylic paint



AL34 is weather-proof paint with high covering capacity for exterior work.

- Low odour
- Resistant to UV rays
- Good adhesion to the substrates
- Resistant to abrasion
- Resistant to alkali

Scope of application

The product is a high quality, decorative coating for exterior mineral surfaces and decorative plasters. It forms an elastic solid surface with a high tolerance to mechanical stress and to aggressive environmental factors. It is resistant to UV rays. EKOFLEKS AL34 is a water-thinnable, with good covering power, thixotropic paint. It possesses good adhesion to the following types of substrates: concrete, sand-lime bricks, cement, lime, cement and gypsum plaster and putty, acrylic plaster, plasterboard, old water-dispersive coatings. It is used both as a coating for new and repair of old coverings. It is easy to use. It is resistant to alkali. The paint can also be used for indoor premises experiencing increased operational load (abrasion, humidity). Paint EKOFLEKS AL34 can be tinted in 180 colours. This paint is not meant for painting wood and metal bases. It is not suitable for horizontal surfaces with mechanical load and water load.

Instructions for use

The surface must be clean and dry, without grease, oils, waxes and other reducing adhesion of materials, as well as, with no visible damage. Surface vegetation or micro-organisms formation must be removed with a wire brush or treated with antibacterial agent, according to the instructions. Prepare the surface for painting, covering it with universal primer EKOFLEKS GL25 or EKOFLEKS GL27. Before use, product EKOFLEKS AL34 has to be mixed thoroughly. Apply paint EKOFLEKS AL34 diluting it with water if necessary (not more than 5%). Apply with a brush, a roller or a spray gun. In order to avoid visible joints of individual sections of the treated surface, the material should be applied in one operation using "fresh over fresh" method. Do not apply at temperatures below +5°C and above +35°C, with strong winds and high humidity. At +20°C and relative humidity of 65%, the coating will be dry on the surface in 2-3 hours and will be ready for overcoating. The coating will be completely dry and able to hold loading in approximately 72 hours. These terms are increasing at a lower temperature and higher humidity. Finishing work, the tools have to be washed immediately with plenty of water. If the paint dries out, it should be washed with organic solvents.

Terms of application and storage

Work should be carried out at substrate temperatures from +5° C to +35° C. It should be stored in an original container, in areas with a constant temperature of +5° C to +30° C. During transportation it has to be protected from freezing. Storage period is 12 months from the manufacture date indicated on the package.

Instructions for disposal

The material cannot be sewered into drains and discharged into wastewater. Plastic packaging is recommended to recycle in special containers for plastic. Material residues after drying can be disposed as construction waste or household garbage.

Security measures

Keep out of reach of children. In case of eye contact, rinse immediately with plenty of water and consult a

AL34 EKOFLEKS - Facade acrylic paint

doctor for medical advice.

Technical data	
Composition:	Aqueous dispersion of polymer, modifiers, mineral fillers
Colour:	180 colors
Temperature of the air and the base:	from +5°C to +35°C
Drying time:	3 to 4 hours
Consumption:	from 0,3 to 0,4 l/m ² , for two coats depending on the surface
Working life:	12 months
Package:	10l; 20l
Made in EU	