

## GL21 EKOFLEKS - BauPrimer - impregnating primer



GL21 is intended for aligning moisture absorption, impregnating and bonding of dusty indoor surfaces

- Colourless
- High binding capacity
- Aligns moisture absorption
- Improves adhesion of coatings to the substrate
- Improves water resistance
- Vapour-permeable
- Environmentally friendly

### Scope of application

Impregnating primer Ekofleks GL21 is used to coat the inside surfaces of walls and ceilings before plastering, puttying, painting and wallpapering. It is suitable for the following substrates: cement and concrete walls and ceilings, cement and plaster, gypsum plasterboard. It is not suitable for priming wood and metal surfaces.

### Instructions for use

The surface should be sturdy and without damage. Loose layers that can not withstand the load must be completely cleaned from the surface by mechanical means. The surface should be dried and cleaned from dust and contaminants which degrade the adhesion to the substrate, as well as the ability to absorb (fats, oils, waxes, bitumen, etc.). In case of biological corrosion (such as a biological entity or the formation of micro-organisms), the surface should be cleaned with a wire brush, and then it should be treated with an antibacterial agent in accordance with the instruction. Do not apply the product on the frozen surface. Before applying, Ekofleks GL21 should be stirred well. Apply with a brush or a roller. For the surface having high absorbency, the primer should be applied in two layers. Subsequent work can be carried out only after the complete drying of the product. Finishing work, the tools have to be washed with water immediately. Dried primer can be removed with the help of an organic solvent.

### Terms of application and storage

Work should be carried out at substrate temperatures from +5°C to +35°C. It should be stored in an original container, in areas with a constant temperature of +5°C to +30°C. During transportation it has to be protected from freezing. Storage period is 12 months from the manufacture date indicated on the package.

### Instructions for disposal

The material cannot be sewered into drains and discharged into wastewater. Plastic packaging is recommended to recycle in special containers for plastic. Material residues after drying can be disposed as construction waste or household garbage. Security measures Keep out of reach of children. In case of eye contact, rinse immediately with plenty of water and consult a doctor for medical advice.

Technical data	
Composition:	Aqueous dispersion of polymer, modifiers
Colour:	Colourless
Temperature of the air and the base:	from +5°C to +35°C
Drying time:	4 to 6 hours

## GL21 EKOFLEKS - BauPrimer - impregnating primer

Technical data	
Consumption:	from 0,1 to 0,2 l/m <sup>2</sup> , depending on the surface porosity
Working life:	12 months
Package:	5l; 10l.
Made in EU	