

## GL24 EKOFLEKS - Stuckprimer - highly absorbent surfaces primer



GL24 is intended for priming porous, highly absorbent surface.

- Reduces the absorbency of the substrate
- Improves adhesion of coatings to the substrate
- Resistant to alkali
- Vapour-permeable
- Environmentally friendly

### Scope of application

The primer Ekofleks GL24 Stuckprimer serves for priming porous, highly absorbent surfaces such as concrete, foam concrete, ceramic and silicate blocks before subsequent applying of gypsum and cement plasters. It lowers and aligns the water absorption of the surface. It has a high adhesive ability.

### Instructions for use

The surface should be sturdy and without damage. Loose layers that cannot withstand the load must be completely cleaned from the surface by mechanical means. The surface should be dried and cleaned from dust and contaminants that degrade the adhesion to the substrate as well as the ability to absorb (fats, oils, waxes, bitumen, etc.). Do not apply the product on the frozen surface! Before applying, product Ekofleks GL24 should be stirred well, and then diluted with water in a ratio of 1:1 to 1:3. Apply using a spray, a brush or a roller. Subsequent work should be carried out only after the complete drying of the product. Finishing work, the tools have to be washed with water immediately. Dried primer can be removed with the help of an organic solvent.

### Terms of application and storage

Work should be carried out at substrate temperatures from +5<sup>0</sup> C to +35<sup>0</sup> C. It should be stored in an original container, in areas with a constant temperature of +5<sup>0</sup> C to +35<sup>0</sup> C. During transportation it has to be protected from freezing. Storage period is 12 months from the manufacture date indicated on the package.

### Instructions for disposal

The material cannot be sewerred into drains and discharged into wastewater. Plastic packaging is recommended to recycle in special containers for plastic. Material residues after drying can be disposed as construction waste or household garbage.

### Security measures

Keep out of reach of children. In case of eye contact, rinse immediately with plenty of water and consult a doctor for medical advice.

Technical data	
Composition:	Aqueous dispersion of polymer, modifiers
Colour:	Yellow
Dilution:	From 1:1 to 1:3
Temperature of the air and the base:	from +5 <sup>0</sup> C to +35 <sup>0</sup> C

## GL24 EKOFLEKS - Stuckprimer - highly absorbent surfaces primer

### Technical data

Drying time:	3 to 6 hours
Consumption:	~ 0,1 l/m <sup>2</sup> (concentrate), depending on surface porosity
Working life:	12 months
Package:	5L; 15L

Made in EU